

Express Mail No. EL664113196US

ATTY. DKT.: P-1656

**UNITED STATES PATENT APPLICATION**

**OF**

**CHAD C. SMUTNEY**

**AND**

**JOHN M. POLIDORO**

**FOR**

**BLUNTABLE NEEDLE ASSEMBLY**

**WITH OPEN-ENDED BLUNTING PROBE**

NCL PRFD. 10/8/00

P-1600s/P-1656/patapp(mf)

09738 4094  
T05070 325260

BLUNTABLE NEEDLE ASSEMBLY  
WITH OPEN-ENDED BLUNTING PROBE

BACKGROUND OF THE INVENTION

5

Field of the Invention

The present invention pertains to self-blunting medical needles and, in particular, to needle assemblies in which an internal blunting component provides a flow path to the surrounding needle housing.

10

Related Art

Many accidental needle-stick wounds are sustained by healthcare workers each day. The problem is aggravated by the trend of moving treatment out of hospitals and into doctors' offices and neighborhood clinics as part of programs to reduce healthcare costs. This trend increases the number and dispersion of healthcare workers who administer injections and draw blood samples, while reducing the frequency of such injections per individual healthcare worker. As a consequence, a larger number of less experienced people are administering injections and/or taking blood samples. Although in the past an occasional serious illness such as that caused by the hepatitis B virus was sustained as a result of an accidental needle-stick wound, the problem was not considered to be a serious one until the advent of human immunodeficiency virus (HIV) and the knowledge that this virus is transmissible to healthcare workers through needle-stick wounds from a contaminated needle. HIV causes acquired immune deficiency syndrome (AIDS) which has already killed millions and infected millions more. HIV is often referred to simply as "the AIDS virus" and the Surgeon General of the United States of America noted in a published (September, 1987) interview that there is no better way to become infected with the AIDS virus than to take blood from an AIDS patient and accidentally inflict a needle-stick wound with the contaminated needle. This situation, and the rising incidence of hepatitis C, another blood-transmissible disease, has stimulated activity to develop devices which reduce or eliminate the possibility of accidental needle-stick wounds without excessively increasing the unit cost of needles.

30

In some prior art blutable needle assemblies, the blunting member is open to fluid flow into a fluid chamber (e.g., a flash chamber) of the needle component by virtue of perforations in the blunting member, while the end of the blunting member is sealed off within a shuttle struc-

ture which is accessible externally of the needle component. For example, U.S. Patent 5,817,060 to Overton et al, issued October 6, 1998 and entitled "Unidirectional Blunting Apparatus For Hypodermic Needles", discloses a blunting apparatus for hypodermic needles. As seen in Figure 5, the needle cannula 26 is mounted in a hub 32 which defines a fluid chamber (bore 34). The blunting member 40 extends into the cannula from a shuttle (positioning member 44). The shuttle is disposed partially within the fluid chamber but it also protrudes outwards to provide a surface 50 by which the blunting member can be moved from outside the chamber. The end of the blunting member is not open for fluid flow to the chamber, so the blunting member is perforated for this purpose (apertures 48). A similar arrangement is seen in U.S. Patent 5,743,882 to Luther, issued April 28, 1998 and entitled "Needle Blunting Assembly For Use With Intravascular Introducers" (see Figures 4 and 5) and in U.S. Patent 5,697,914 to Brimhall, issued December 16, 1997 and entitled "Control Forward/Flashback Forward One Hand Introducer Needle and Catheter Assembly", although in the Brimhall Patent the relative positions of the catheter (which is analogous to a blunting member) and the needle cannula are reversed (see Figure 2).

In other prior art assemblies, the end of the blunting member is open to fluid flow into the needle component chamber, but the shuttle is wholly enclosed within the needle component. For example, the Bio-Plexus, Inc. Patent to Burzynski et al, U.S. 5,951,520, issued September 14, 1999 and entitled "Self-Blunting Needle Medical Devices And Methods Of Manufacture Thereof", discloses a self-blunting needle assembly in which the needle component defines a fluid chamber (within syringe body 102) and the end of the blunting component is open to fluid flow to the chamber. However, the blunting component shuttle (hub 16) does not extend outside the fluid chamber for access from outside the chamber.

In still other prior art devices, the end of the blunting member is open and fluid can flow therethrough but there is no fluid flow communication from the blunting member to a fluid chamber on the needle holder or the blunting member shuttle. This configuration is illustrated in U.S. Patent 4,627,841 to Dorr, issued December 9, 1986 and entitled "Infusion Needle", where it is seen that the blunting component or "catheter" 17 is mounted in a bore in hub 12 which perforates, i.e., extends through, the hub and therefore has two open ends. Catheter 17 is disposed concentrically within needle cannula 14 and the rearward end 19 open for fluid flow. However, the needle holder (hub 11, Figure 4) and hub 12 do not define a flash chamber and the open end of the blunting component.

## SUMMARY OF THE INVENTION

The present invention pertains to a bluntable needle assembly comprising a needle component comprising a housing and a needle cannula mounted on the housing, the housing defining a fluid chamber and an access port for fluid flow therethrough. There is a blunting component comprising a shuttle member and a blunting probe mounted on the shuttle member, the blunting probe having a blunt tip and a rearward open end. The blunting probe is disposed within the needle cannula and the needle component and the blunting component are configured with the blunting probe within the needle cannula for movement from a sharpened configuration to locking engagement in a blunted configuration, and the shuttle member is configured to extend outside the fluid chamber and to permit fluid flow from the open end of the blunting probe into the fluid chamber.

According to one aspect of the invention, the blunting probe may be tubular and non-perforated.

According to another aspect of this invention, the needle assembly may comprise a detent and a stay, the detent being movable between (i) a locking position in which it may bear against the stay and prevent the needle assembly from moving to the sharpened configuration and (ii) an unlocked position which permits the needle assembly to move to the sharpened configuration. Optionally, the shuttle may comprise the movable detent. Another optional feature of the invention is that the detent further comprises a coupling site for engagement by an accessory.

The housing may define a port into which a piston portion of the shuttle extends from outside the fluid chamber.

In one embodiment, the shuttle member may define a non-perforating cavity within which the blunting probe is mounted. In another embodiment, the shuttle member may be perforated to permit fluid flow from the open end of the blunting probe therein to the fluid chamber. In yet another embodiment, the shuttle member may comprise an extension connected to the blunting probe in a manner which permits fluid flow from the end of the blunting probe to the fluid chamber.

According to yet another aspect of this invention, a bluntable needle assembly may comprise a needle component comprising a housing and a needle cannula having a sharp tip mounted thereon, and a blunting component comprising a shuttle member with a blunting probe thereon. The shuttle member may define a fluid chamber and an access port for fluid flow therethrough. The blunting probe may have a blunt tip and a rearward end open to the fluid

chamber. As with other embodiments described herein, the blunting probe is disposed within the needle cannula and the needle component and blunting component are configured for movement between a blunted configuration and a sharpened configuration.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1A is a schematic, partially cross-sectional view of a needle component configured for use in a particular embodiment of the present invention;

Figure 1B is a schematic elevational view of the needle component of Figure 1A, taken along line 1B-1B;

Figure 2A is a schematic cross-sectional view of a particular embodiment of a blunting component for use with the needle component of Figure 1A;

Figure 2B is a perspective view of a blunting component intended for use with the needle component of Figure 1A;

Figure 3 is a schematic cross-sectional view of a needle assembly comprising the needle component of Figure 1A and the blunting component of Figure 2A;

Figures 4A and 4B are schematic cross-sectional views illustrating the operation of a release accessory with the detent of the blunting component of Figure 2A;

Figures 5A and 5B are schematic cross-sectional views of a self-blunting catheter assembly in accordance with one embodiment of the invention, comprising the needle assembly of Figure 3 in the blunted and released configurations, respectively;

Figure 6 is a partial cross-sectional view of a blunting probe and the piston portion of a shuttle member in accordance with another embodiment of the invention;

Figures 7 and 8 are partial perspective views of blunting probes and piston portions of shuttle members in accordance with two further embodiments of the invention; and

Figure 9 is a schematic cross-sectional view of a blunting component for a needle assembly according to still another embodiment of this invention.

## DETAILED DESCRIPTION OF THE INVENTION AND PREFERRED EMBODIMENT THEREOF

The present invention pertains to the configuration of a hollow, open-ended blunting probe mounted on a shuttle structure in a needle assembly such that the end of the blunting probe is open for fluid flow. According to one embodiment of the invention, the end of the blunting probe is secured in a non-perforating cavity (e.g., a slot, well, etc.) formed in the shut-

the structure. According to another embodiment, the blunting probe may simply be attached to the shuttle structure in a manner which leaves the end of the blunting probe open. According to still another embodiment, the blunting probe may be mounted in a bore which perforates the shuttle member to provide a flow path through the shuttle member. In each of these embodi-  
5 ments, the needle assembly comprises a fluid chamber into which fluid may flow from the open end of the blunting probe. The fluid chamber may be formed in the housing on which the needle is mounted or on the shuttle structure. The needle component and the blunting component of the needle assembly are preferably configured so that the blunting probe can be received tele-  
10 scopically within the needle cannula and can be moved from a blunting position in which the blunt end of the blunting probe protrudes forward beyond the insertion tip of the needle, to blunt the assembly, and a retracted position (the "sharpened configuration") in which the blunt tip of the blunting probe is withdrawn rearward into the needle, leaving the sharp needle tip ex-  
posed.

Since the open end of the blunting probe is open even though it is joined to the shuttle  
15 structure, the present invention can optionally be practiced with a non-perforated blunting probe (i.e., the blunting probe may consist of a hollow tube open only at the ends) and will still provide fluid flow from the blunting probe to the fluid chamber. This is advantageous because the step of perforating a blunting probe to permit such flow through the probe wall is an expensive processing step which may be omitted by the practice of the invention.

20 This invention can be embodied in various needle devices, including introducer needles for peripherally inserted central catheters. One embodiment of a needle component for a device in accordance with the present invention is shown in Figures 1A and 1B. Needle component 10 comprises a needle cannula 12 mounted in a housing 16. Needle cannula 12 has a sharp puncture tip 14 for penetrating a patient's skin and other tissues and a passageway (unnumbered) that  
25 extends through the cannula and which opens into a chamber 16a in housing 16. Needle component 10 is preferably dimensioned and configured to facilitate the handling of needle cannula 12 for convenient connection to other devices and may include structural features intended for specific environments of use. For example, when the device is intended for use in introducing a venal or arterial catheter, housing 16 may comprise a fluid chamber 20 into which blood can  
30 flow from needle cannula 12. Preferably, at least a portion of housing 16 is translucent or transparent so that the user can see blood flow into chamber 20 as a signal that needle cannula 12 is properly positioned, i.e., housing 16 may comprise a flash chamber for blood flash visualization. Optionally, chamber 20 may have an access port 21 for fluid flow therethrough. Port

21 is preferably configured to receive other devices such as a dosage syringe or fluid delivery tube or for luer access. Housing 16 also defines a port 18a for receiving the blunting component 26 (Figure 2A) as described further below.

Needle component 10 (Figures 1A, 1B) may optionally be configured for a locking engagement with a blunting component. In the illustrated embodiment, needle component 10 comprises a stay 22 that will engage a blunting component as described below. Stay 22 may be positioned at any convenient point on needle component 10 but, in the illustrated embodiment, stay 22 is formed as the shoulder at the end of a sloped incline in a U-shaped guide 24 that is on housing 16 but outside of the chamber 16a.

Needle component 10 defines a port 18a which is preferably fitted with a bushing 54, for receiving the blunting component and through which a blunting probe may be inserted into needle cannula 12 via chamber 16a, as described below. Bushing 54 is an O-ring providing both a sealing function and a guiding function.

A blunting component in accordance with one embodiment of the present invention suitable for use with needle component 10 is shown in Figures 2A and 2B. Blunting component 26 comprises a hollow, unperforated blunting probe 28 that has a distal, open blunt tip 28a and an opposite open end 28b. Blunting probe 28 is carried on a shuttle 30. Shuttle 30 comprises a piston portion 30a and a base portion 32 which comprises a resilient, spring-like detent 34. Shuttle 30 has, in piston portion 30a, a non-perforating cavity for receiving the blunting probe 28. The non-perforating cavity comprises a slot 30b sized to receive blunting probe 28 therein. A bead of adhesive may be applied to blunting probe 28, near the open end and blunting probe 28 may then be positioned in slot 30b. The type and amount of adhesive 30c and the size of slot 30b and of blunting probe 28 which permit blunting probe 28 to be mounted in slot 30b without causing the adhesive to occlude the open end of blunting probe 28 can be readily determined by one of ordinary skill in the art without undue experimentation. Blunting probe 28 is disposed in slot 30b with its end open for fluid flow through slot 30b and the adhesive is then cured. A UV-curable adhesive has been found to work well in this approach, but any other type of suitable adhesive may be used. Thus, open end 28b is open to fluid flow into the slot and, from the slot, into a surrounding region in the needle member, as will be described further below.

Blunting probe 28 (Figure 2A) is configured so that it can be inserted into probe port 18a (Figure 1A) and thus be telescopically disposed within needle cannula 12. Piston portion 30a on shuttle 30 is configured to be movably received in port 18a (Figures 1A and 1B) and to form a seal with port 18a about bushing 54. The piston portion 30a thus extends into chamber

16a (Figure 1A). Base portion 32 extends outside of chamber 16a where it carries detent 34 which comprises a lug 34a that is dimensioned and configured to engage stay 22 of needle component 10 (Figures 1A and 1B), as will be described below. Detent 34 also carries a coupling site 34b defined by an oblique flange 36 and a coupling shoulder 38. Shuttle 30 (Figure 2A) is dimensioned and configured so that when blunting probe 28 is thus inserted into needle cannula 12 (Figure 1A), detent 34 can be received within guide 24 and can move axially within channel 24a. The portions of shuttle 30 outside fluid chamber 20 are used to control the movement of the shuttle 30 and the blunting probe 28 thereon relative to the needle component 10. Shuttle 30 and guide 24 are dimensioned and configured so that detent 34 is biased to engage stay 22. Detent 34 is movable between a locking position in which it inhibits movement of the blunting component to an unlocked position in which it permits movement of the blunting component, as described further herein. Thus, needle component 10 and blunting component 30 can be assembled to produce a self-blunting needle assembly 40 shown in Figure 3. Figure 3 shows needle assembly 40 in the blunted configuration, i.e., with blunting probe 28 disposed telescopically within needle 12 and positioned therein so that blunt tip 28a protrudes beyond puncture tip 14 and thus blunts needle assembly 40. As illustrated in Figure 3, lug 34a on blunting component 26 (Figures 2A and 2B) outside of chamber 16a (Figure 1A) engages stay 22 on needle component 10. Accordingly, even if axial pressure is applied on blunt tip 28a, movement of blunt tip 28a into needle cannula 12 (exposing puncture tip 14) is prevented because lug 34a of detent 34 bears against stay 22, thus preventing rearward axial movement (as sensed relative to needle cannula 12) of blunting probe 28. Thus, needle assembly 40 is locked in the blunted configuration in which it will protect users against accidental needle sticks. However, needle assembly 40 is releasably locked in the blunted configuration. To release the blunting component in needle assembly 40 as shown in Figure 3, it is necessary to disengage lug 34a from stay 22. In the particular illustrated embodiment, guide 24 is dimensioned and configured to permit the flexure of detent 34 to permit lug 34a to be moved upward (as sensed in Figure 3) for a distance sufficient to disengage lug 34a from stay 22. Once detent 34 has been flexed in this manner, blunting component 26 is free to slide within guide 24 for a distance sufficient for blunt tip 28a to be withdrawn into needle cannula 12, thus exposing puncture tip 14.

Guide 24 is open-ended so that detent 34 is accessible from outside guide 24. Coupling site 34b on detent 34 is especially accessible and is dimensioned and configured to engage an accessory device that is used to raise lug 34a away from stay 22. A suitable accessory is partially illustrated in Figures 4A and 4B. Accessory 42 carries a pawl 44 that is dimensioned and



configured to enter channel 24a (Figure 3) and to engage coupling site 34b. In particular, pawl 44 initially engages flange 36. Due to the slanted internal configuration of flange 36, movement of accessory 42 in a substantially rearward direction causes flange 36 to rise, as sensed in Figure 4A, thus flexing detent 34 and lifting lug 34a, as indicated by the unnumbered arrows in Figure 4A. Flange 36 and coupling site 34b are dimensioned and configured so that the rearward movement of accessory 42 flexes detent 34 to a degree sufficient to disengage lug 34a from stay 22 (shown in Figure 3). When pawl 44 is fully received within flange 36, a coupling surface 44a on pawl 44 is disposed against coupling shoulder 38, as shown in Figure 4B, which shows the elevated, disengaged (i.e., released) position of detent 34 and, in dotted outline, the locked position of detent 34. One advantage of the illustrated embodiment is that the releasable locking mechanism is enclosed within guide 24, thus reducing the likelihood of inadvertent release of blunting component 26, that could lead to, or allow, an accidental needle stick.

In some embodiments, such as a Y-line connector, an accessory has an injection port dimensioned and configured to receive the needle assembly and engage the coupling site. In other embodiments, such as a catheter, the catheter hub is dimensioned and configured to receive the needle assembly and engage the coupling site.

In a particular embodiment, an accessory may comprise part of a catheter assembly comprising a catheter hub on the end of a catheter tube. The catheter tube is sized to receive the needle cannula therein and the catheter hub is dimensioned and configured to engage the hub portion of the needle component. Thus, as shown in Figure 5A, needle cannula 12, blunted by blunt tip 28a of blunting probe 28, is inserted into and through catheter 46. Catheter 46 comprises a catheter tube 46a and a catheter hub 46b which is dimensioned and configured to receive hub portion 18 of needle component 10. Hub 46b comprises an accessory flange 46c that is dimensioned and configured to enter U-shaped guide 24 and to engage the coupling site 34b on detent 34 as shown in Figures 4A and 4B.

The combination of catheter 46 and needle assembly 40 constitutes an accessory-needle apparatus in accordance with one embodiment of the present invention.

Catheter 46 and needle assembly 40 are dimensioned and configured so that, when catheter 46 is fully mounted on hub portion 18 of needle component 10, the end of catheter 46 is drawn past the puncture tip of needle cannula 12. To fully mount catheter 46 on needle assembly 40, catheter hub 46b is moved axially rearward along needle cannula 12. Such motion causes accessory flange 46c to engage coupling site 34b as shown in Figures 4A and 4B. Once accessory flange 46c engages coupling site 34b, a slight rearward motion of catheter hub 46b

disengages lug 34a from stay 22. Further rearward motion of catheter tube 46 towards full engagement with needle component 10, as shown in Figure 5B, moves blunting component 26 rearwardly (i.e., away from puncture tip 14 of needle cannula 12) and draws blunt tip 28a of blunting probe 28 into needle cannula 12, thus exposing puncture tip 14. As indicated above, blunting probe 28 is hollow and open only at the ends. Needle assembly 40 is configured, however, so that even when it is in the sharpened configuration shown in Figure 5B, fluid can flow out of open end 28b, through slot 30b and into fluid chamber 20 of needle component 10.

In use, the fully assembled apparatus 50 in the sharpened configuration of Figure 5B can be used to effect venipuncture with puncture tip 14 to introduce catheter tube 46 into the vein. Proper positioning of needle 12 into the vein is indicated by the flow of blood through needle cannula 12, into hollow blunting probe 28 and out the open end 28b (Figure 2A) thereof, through slot 30b (Figure 2A) and through access opening 52 (Figure 5B) in needle component 10 to fluid chamber 20. As indicated above, needle component 10 comprises bushing 54 that is dimensioned and configured to engage shuttle 30 in a manner that permits movement of blunting component 26 between sharpened and blunted configurations while preventing fluid flow into U-shaped guide 24. This aspect of this invention thus pertains to an assembly in which the blunting component shuttle is disposed partially within a fluid chamber in the assembly, and is configured to extend from the interior of the fluid chamber to its exterior so that the blunting component can be manipulated by contact with a structure outside the chamber. In the embodiment illustrated, it is shuttle 30 which is dimensioned and configured for this purpose, but other embodiments will be obvious to those skilled in the art, after reading this disclosure.

After the catheter 46 is positioned as desired within the patient's vein, the needle assembly 40 is withdrawn from catheter 46. As needle component 10 is withdrawn from catheter hub 46b, accessory flange 46c pulls blunting component 26 forward in needle component 10 (i.e., towards puncture tip 14) by engaging coupling shoulder 38 (Figure 4B). As lug 34a slides past stay 22 and needle assembly 40 is further withdrawn from catheter 46, lug 34a is moved into position to engage stay 22 and accessory flange 46c is disengaged from coupling site 34b. Accordingly, spring-like detent 34 moves downward, causing lug 34a to engage stay 22. This locks blunting component 26 in needle component 10 in the blunted configuration, i.e., with blunt tip 28a of blunting probe 28 extending beyond puncture tip 14. Due to the length of needle cannula 12 and blunting probe 28, needle assembly 40 becomes locked in the blunted configuration even before needle cannula 12 is fully withdrawn from catheter 46.

The location of stay 22 (Figure 1A) and corresponding lug 34a (Figure 2A) can be varied as matters of mere design choice. In addition, a variety of locking mechanisms that are releasable by the use of an accessory into which the needle is inserted can be employed.

The present invention can be practiced in various alternative embodiments, all of which permit fluid to flow from the open end of the blunting probe into the needle member chamber. For example, the piston portion of the blunting member shuttle, instead of being slotted, may be perforated by a two-ended bore as suggested in Figure 6. In such an embodiment, the open end of blunting probe 28 is inserted into the opening of bore 30b' at the forward end of piston portion 30a'. Bore 30b' permits fluid to flow therethrough from the open end of blunting probe 28 to the needle component chamber. Optionally, the blunting probe may extend through the perforation in the piston portion so that fluid appears to flow directly from the open end of the blunting probe into the needle chamber. In an alternative embodiment, the cavity into which blunting probe 28 is inserted may be a non-perforating well configured to permit fluid to flow out the open end of blunting probe 28 and then forward along the blunting probe 28 and out the end of the piston portion, as suggested in Figure 7.

Figure 8 shows an alternative configuration in which the piston portion 30a" carries a mounting extension 31a shaped like a chisel blade which is configured to be inserted and secured within the open end 28b of blunting probe 28 without blocking fluid flow therethrough. Various other mounting extensions can be used to permit the blunting member to be advanced and retracted by movement of the shuttle without obstructing fluid flow from the open end thereof into the fluid chamber of the needle member. For example, the mounting extension may be in the form of a helical spring, a substantially straight wire or rod, etc., joining the piston portion to the blunting probe without obstructing fluid flow from the end of the blunting probe.

A blunting component for a needle assembly in accordance with yet another embodiment of the present invention is shown in Figure 9. Blunting component 126 comprises a shuttle 130 on which is carried a blunting probe 128. Blunting probe 128 is hollow and open at both ends but is otherwise unperforated. Blunting probe 128 is mounted on shuttle 130 with an open end open for fluid flow to fluid chamber 116. Chamber 116 may define an opening 121 having a standard configuration for connection to other devices, e.g., a luer access. Optionally, part of the structure defining chamber 116 may be transparent or translucent, thus allowing chamber 116 to serve as a flash chamber. Shuttle 130 comprises a detent 134 which is configured for a releasable locking engagement with a needle component and, optionally, for engagement with an accessory device such as a catheter, in substantially the same manner as detent 34

(Figure 2A) of shuttle 30. Thus, blunting component 126 and a complementary needle component can be configured so that blunting probe 128 is inserted into a needle cannula and is movable between a blunted configuration and a sharpened configuration, in substantially the same manner as apparatus 50, Figures 5A and 5B.

5           As is evident from Figure 9, blunting probe 128 is mounted in a bore which perforates shuttle 130.

          While the invention has been described in detail with reference to particular embodiments thereof, it will be apparent upon a reading and understanding of the foregoing, that numerous alterations and variations to the described embodiments may occur to those skilled in  
10       the art, and that such alterations and variations will lie within the scope of the appended claims.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2